



REDGUM RGSW6 Subwoofer Amplifier Plate

.....when you want the Subwoofer amplifier that other manufacturer's choose.

Bass weight and Extension are the key words.

For installation in fixed installation, DIY or existing passive subwoofers.

- ✍ Substantial 1100WRMS power output into 4 ohm
- ✍ 1000va toroidal transformer
- ✍ Fully sealed plate for installation direct into subwoofer enclosure wall
- ✍ Electronic Crossover adjustable from 20Hz to 200Hz
- ✍ Highly stable, Audiophile quality MOSFET output stages
- ✍ Phase reversal switch for ease of position adjustment
- ✍ Level control to allow matching with a wide range of Home Theatre systems
- ✍ 'Always On' allows for instant operation with no 'warm-up' period
- ✍ Power switch incorporates overload circuit-breaker with 'trip' light
- ✍ Attractive slimline design
- ✍ Optional Hi-Level input board to allow connection direct to speaker lines

REDGUM RGSW Amplifier Plate - Stunning!!

RGSW6 - 1000VA Subwoofer Amplifier Plate

1 year Warranty

Power Output:

1100 into 4 ohms

Frequency Response:

(relative to 20Hz/0db) minus 3db points are 1 Hz

adjustable from 20 to 200Hz

Electronic Crossover:

variable from 20 to 200Hz at slope 6db/ octave

Damping Factor:

> 1600

Input Sensitivity:

220mV for 175W RMS (adjustable from 100mV to 25V)

Signal to Noise (output stage)

> 110db

Signal to Noise (overall):

> 85db

Slew Rate:

35V / uS

Input Impedance

10k ohms

Plate Finish:

2mm high gloss Powder coated Steel plate with Matt black heatsink

Plate Dimensions:

270mm (H) x400mm (W) x (80 internal + 45 external)mm (D)

Shipping weight:

11 kg